



newsworks newsworks newsworks newsw



Amazingly simple new way to change wheels

The Original Wheel Guide empowers you to change alloy road wheels fast. Instead of straining yourself or getting down on your knees or sitting on the ground balancing a wheel between your feet, simply insert the Original Wheel Guide through a stud hole in the wheel and slide it onto its mount in seconds. No sweat!

Features:

- To accommodate the four most popular wheel stud sizes, Original Wheel Guides are available in 7/16in or 1/2in or 12mm or 14mm.
- A complete kit of wheel guides featuring all four sizes is also available.
- Made from thin-wall stainless steel tubes
- Patent-pending, these new Original Wheel Guides are priced at \$29.95 each or \$114.95 for the kit of four (plus shipping).



For more information contact:

Byron Tool Company, LLC

Cumming, Georgia,

Telephone (678) 744-7253 or e-mail:

WheelGuideSales@gmail.com

Visit the Original Wheel Guide website at:

www.OriginalWheelGuide.com

Instructions

1. Position hub with one wheel stud near top dead center.
2. With a bolt hole near top dead center, position the wheel about 6-7 inches from the hub (allowing 3-4 inches at the end of wheel guide for gripping), and slip the wheel guide through the hole, engaging its inner end on the top wheel stud.
3. Slightly lift the outer end of the wheel guide and using the side of your foot slide the wheel onto the studs.
4. If necessary, use the wheel guide under the tire to raise the wheel onto its hub register.

